



PROJECT	DATE
TYPE	CATALOG #

PREMIUM SS OPEN FACE

CW04L IN-GROUND WELL LIGHT

KEY FEATURES

- HEAVY GAUGE STAINLESS STEEL (TOP), FIBERGLASS OR STAINLESS STEEL BOTTOM

- DIMMABLE* (TRANSFORMER USED MUST BE DIMMABLE)
- TEMPERED, SHOCK AND HEAT RESISTENT LENS
- FIELD REPLACEABLE LED

PRODUCT SPECIFICATIONS

MATERIAL	STAINLESS STEEL (TOP), FIBERGLASS (BOTTOM)
LENS	CLEAR TEMPERED GLASS
VOLTAGE	12V AC/DC
ILLUMINATION	UP TO 40 FT
IP RATING	IP68 SUBMERSIBLE / WET LOCATION

STEP 1

FIXTURE CONFIGURATION

CW04L

FINISH

SS - STAINLESS STEEL

STEP 3

ACCESSORY OPTIONS

PVC SLEEVE
OPTIONAL

OPTION

PVC-SLEEVE EXTERNAL PVC PRE-MOUNT SLEEVE

STEP 2

LED LAMP CONFIGURATION

LED

LED WATTAGE

3W 280 LM

5W 400 LM

7W 550 LM

12W 850 LM

KELVIN TEMPERATURE

27K 2700K

30K 3000K

40K 4000K

50K 5000K

BEAM ANGLE

18D 18° NARROW

38D 38° STANDARD

60D 60° WIDE