



Projects:
Comments:

CW37L - FIBERGLASS COMPOSITE 120V/277V LED OPEN FACE IN-GROUND WELL LIGHT

SPECIFICATIONS:

WATTAGES:	11W, 15W, 20W, 30W or 50W
MODEL #:	CW37L
LISTINGS	CE RoHS, TUV, FCC
VOLTAGE:	100V~130V, 170V~240V or 265V~277V AC
POWER FACTOR:	>0.95
FREQUENCY:	50-60Hz
LUMENS:	900 to 4,500 Lumens (depending on wattage)
LUMENS EFFICACY:	>80 Lm/W
KELVIN (CCT):	2700K, 3000K, 4000K, 5000K, RGBW (Opt.)
THD:	14.7%
CRI:	>80
IP RATING:	IP65 Outdoor / Wet Location Use
BEAM ANGLE (DEGREE):	25°, 40°, 110° (Consult Factory for others)
MOUNTING:	In-Ground Mounting
MATERIALS:	Fiberglass Composite Top With Tempered Glass
USED FOR:	Commercial / Residential Landscapes
APPLICATIONS:	Wall Washing, Tree / Flag Pole Uplighting, etc.
LIFE SPAN (HOURS):	50,000+ Hours
DIMMING COMPATIBLE:	Dimmable (depending on LED options, consult
LENGTH OF WARRANTY (YEARS):	Lifetime (Fixture), 5 years (LED components)
WORKING ENVIRONMENT:	-34°C to +50°C (-30°F to +122°F)
SUGGESTED REPLACEMENT FOR:	90-500 Watt Halogen (30-175W Metal Halide)

