

Projects:

Comments:

## CW38L - FIBERGLASS COMPOSITE 120V/277V LED LOUVERED FACE IN-GROUND WELL LIGHT

### SPECIFICATIONS:

<b>WATTAGES:</b>	11W, 15W, 20W, 30W or 50W
<b>MODEL #:</b>	CW38L
<b>LISTINGS</b>	CE RoHS, TUV, FCC
<b>VOLTAGE:</b>	100V~130V, 170V~240V or 265V~277V AC
<b>POWER FACTOR:</b>	>0.95
<b>FREQUENCY:</b>	50-60Hz
<b>LUMENS:</b>	900 to 4,500 Lumens (depending on wattage)
<b>LUMENS EFFICACY:</b>	>80 Lm/W
<b>KELVIN (CCT):</b>	2700K, 3000K, 4000K, 5000K, RGBW (Opt.)
<b>THD:</b>	14.7%
<b>CRI:</b>	>80
<b>IP RATING:</b>	IP65 Outdoor / Wet Location Use
<b>BEAM ANGLE (DEGREE):</b>	25°, 40°, 110° (Consult Factory for others)
<b>MOUNTING:</b>	In-Ground Mounting
<b>MATERIALS:</b>	Fiberglass Composite Top With Tempered Glass
<b>USED FOR:</b>	Commercial / Residential Landscapes
<b>APPLICATIONS:</b>	Wall Washing, Tree / Flag Pole Uplighting, etc.
<b>LIFE SPAN (HOURS):</b>	50,000+ Hours
<b>DIMMING COMPATIBLE:</b>	Dimmable (depending on LED options, consult
<b>LENGTH OF WARRANTY (YEARS):</b>	Lifetime (Fixture), 5 years (LED components)
<b>WORKING ENVIRONMENT:</b>	-34°C to +50°C (-30°F to +122°F)
<b>SUGGESTED REPLACEMENT FOR:</b>	90-500 Watt Halogen (30-175W Metal Halide)

