

Projects:

Comments:

CW54L - BRASS / COMPOSITE 120V/277V LED OPEN FACE IN-GROUND WELL LIGHT

SPECIFICATIONS:

| | |
|------------------------------------|---|
| WATTAGES: | 15W, 20W, 30W or 50W |
| MODEL #: | CW54L |
| LISTINGS | CE RoHS, TUV, FCC |
| VOLTAGE: | 100V~130V or 170V~277V AC |
| POWER FACTOR: | >0.95 |
| FREQUENCY: | 50-60Hz |
| LUMENS: | 900 to 4,500 Lumens (depending on wattage) |
| LUMENS EFFICACY: | >80 Lm/W |
| KELVIN (CCT): | 2700K, 3000K, 4000K, 5000K, RGBW (Opt.) |
| THD: | 14.7% |
| CRI: | >80 |
| IP RATING: | IP65 Outdoor / Wet Location Use |
| BEAM ANGLE (DEGREE): | 25°, 40°, 110° (Consult Factory for others) |
| MOUNTING: | In-Ground Mounting |
| MATERIALS: | Brass Top / Composite Body |
| USED FOR: | Commercial / Residential Landscapes |
| APPLICATIONS: | Wall Washing, Tree / Flag Pole Uplighting, etc. |
| LIFE SPAN (HOURS): | 50,000+ Hours |
| DIMMING COMPATIBLE: | Dimmable (depending on LED options, consult |
| LENGTH OF WARRANTY (YEARS): | Lifetime (Fixture), 5 years (LED components) |
| WORKING ENVIRONMENT: | -34°C to +50°C (-30°F to +122°F) |
| SUGGESTED REPLACEMENT FOR: | 90-500 Watt Halogen (30-175W Metal Halide) |

