



PROJECT	DATE
TYPE	CATALOG #

LITTLE WILL OPEN FACE 120V

SRW-601CB-LED120V IN-GROUND WELL LIGHT

KEY FEATURES

- HEAVY GAUGE DIE-CAST BRASS (TOP), FIBERGLASS BOTTOM
- NATURAL BRONZE FINISH (OTHER FINISHES AVAILABLE, CONSULT FACTORY)

- DIMMABLE* (6 WATT MODEL)
- TEMPERED, SHOCK AND HEAT RESISTENT LENS
- FIELD REPLACEABLE LED

PRODUCT SPECIFICATIONS

MATERIAL	CAST BRASS (TOP), FIBERGLASS (BOTTOM)
LENS	CLEAR TEMPERED GLASS
VOLTAGE	120VAC LINE VOLTAGE
ILLUMINATION	UP TO 30 FT
LEAD WIRE	39"

STEP 1

FIXTURE CONFIGURATION

SRW-601CB-LED120V

FINISH

BZ - BRONZE

CST - CUSTOM

STEP 3

ACCESSORY OPTIONS

PVC SLEEVE
OPTIONAL

OPTION

PVC-SLEEVE

EXTERNAL PVC PRE-MOUNT SLEEVE

STEP 2

LED LAMP CONFIGURATION

LED-120V

LED WATTAGE

3.5W 300 LM

6W 500 LM

KELVIN TEMPERATURE

30K 3000K

50K 5000K

BEAM ANGLE

38D 38° NARROW FLOOD