



PROJECT	DATE
TYPE	CATALOG #

# LITTLE WILL SS LOUVERED FACE

## SRW-602SS-LED IN-GROUND WELL LIGHT

### KEY FEATURES

- HEAVY GAUGE STAINLESS STEEL (TOP), FIBERGLASS BOTTOM •UNFINISHED STAINLESS STEEL

- DIMMABLE\* (TRANSFORMER USED MUST BE DIMMABLE)
- TEMPERED, SHOCK AND HEAT RESISTENT LENS
- FIELD REPLACEABLE LED

### PRODUCT SPECIFICATIONS

MATERIAL	STAINLESS STEEL (TOP), FIBERGLASS (BOTTOM)
LENS	CLEAR TEMPERED GLASS
VOLTAGE	12V AC/DC
ILLUMINATION	UP TO 40 FT
LEAD WIRE	39"

### STEP 1

#### FIXTURE CONFIGURATION

**SRW-602SS-LED**

#### FINISH

SS - STAINLESS STEEL

### STEP 3

#### ACCESSORY OPTIONS

**PVC SLEEVE**  
OPTIONAL



OPTION

PVC-SLEEVE      EXTERNAL PVC PRE-MOUNT SLEEVE

### STEP 2

#### LED LAMP CONFIGURATION

<b>LED</b>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
LED WATTAGE	3W 280 LM	5W 400 LM	7W 550 LM
	12W 850 LM		
KELVIN TEMPERATURE	27K 2700K	30K 3000K	40K 4000K
	50K 5000K		
BEAM ANGLE	18D 18° NARROW	38D 38° STANDARD	60D 60° WIDE