Project Name:	Notes:	Date:	Туре:

DESCRIPTION

Our Baylux Flat linear high bay is our workhorse fixture and is consistently one of our best-selling products. Need a motion sensor or emergency battery back-up? We got you covered!

Ideal use for large indoor areas, warehouses, parking garages, walkways, school/campuses, shopping centers and commercial areas.



CONSTRUCTION

Traditional design using high standard aluminum alloy body with a white finish.

FI FCTRICAL

Luminaire is built with the highest quality 100-277VAC drivers (custom order available for 347-480VAC driver).

OPTICAL SYSTEM

Designed to reduce glare and improved light distribution through precision formed lens optics.

ENERGY SAVINGS

50% more energy savings that fluorescent fixtures. Low heat production requires less air-conditioning requirements.

DIMMING

1-10V dimmable standard

LISTING

UL Listed, FCC, RoHS, CE, DLC Premium Listed, With LM79 & LM80











TECHNICAL SPECIFICATION


TECHNICAL SPECIFICATION				
WATTAGE	110W			
LUMENS	16,500 Lumens			
EFFICACY	150 Lm/W			
VOLTAGE	AC100-277V (347-480V custom order)			
POWER FREQUENCY	50/60 Hz			
CCT	5000K			
CRI	Ra>80			
BEAM ANGLE	110°			
WORKING TEMP.	-4°F - +104°C			
STORAGE TEMP.	-22°F - +140°C			
IP RATING	IP40, Suitable for damp locations			
DIMMABLE	1-10V dimming			
POWER FACTOR	>0.9			
THD	<15%			
WARRANTY	10 year limited			

MODEL NUMBER(S)								
MODEL#	WATTS	LUMENS	LM/WATT	CCT	CRI	VOLTAGE		
LHF09	90W	12,600	140	5000K or 4000K	>80	AC 100/277V		
LHF11	110W	16,500	150	5000K	>80	AC 100/277V		
LHF16	160W	22,400	140	5000K or 4000K	>80	AC 100/277V		
LHF22	220W	30,800	140	5000K or 4000K	>80	AC 100/277V		
LHF32	320W	44,800	140	5000K or 4000K	>80	AC 100/277V		

Project Name:	Notes:	Date:	Type:

DIMENSIONS

WIRE GUARD OPTION



LHF09-11-WGWire guard for LHF09 & LHF11

AVAILABLE OPTIONS



LHF-00MS On/Off Motion Sensor



LHF-BLDMSFully Dimmable, Daylight
Harvesting Motion Sensor




LHF-MCRC Motion Sensor Remote Control (Needed to program the motion sensor)



EMERGENCY BATTERY BACK-UP (Please inquire for more info)

PHOTOMETRICS (110W Photometrics shown below)



Average Beam Angle (50%): 106.6 degree