



MSL4W-50K-BZ
MSL4W-30K-BZ
MSL4W-50K-WH
MSL4W-30K-WH

NEXGEN™ 40W DIMMABLE LED SECURITY LIGHTS

Ideal for doorway, pathway and alleys. Great for use with optional motion sensors or photocell.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120VAC, 50/60Hz
- Wattage: 40W
- Power Factor: 0.90~0.97
- Efficacy: 120LM/W

HOUSING SPECIFICATIONS:

- Housing: Die-cast aluminum with powder coat finish
- Mounts flush on wall or 4" round weatherproof box
- Can be installed with any standard LED dimmers (TRIAC types)
- Operating Temperature: -40°F~104°F
- IP Rating: IP65, Suitable for wet locations

CERTIFICATIONS: ETL



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
MSL4W-50K-BZ	40W	120VAC	4800LM	5000K
MSL4W-30K-BZ	40W	120VAC	4800LM	3000K
MSL4W-50K-WH	40W	120VAC	4800LM	5000K
MSL4W-30K-WH	40W	120VAC	4800LM	3000K

OPTIONAL MOTION SENSORS & PHOTOCELL:



MODEL	DESCRIPTION
MS180-WH	120V AC, 180°, 200W Max Load, OUTDOOR MOTION SENSOR (WHITE)
MS180-BZ	120V AC, 180°, 200W Max Load, OUTDOOR MOTION SENSOR (BRONZE)
MS240-WH	120V AC, 240°, 500W Max Load, OUTDOOR MOTION SENSOR (WHIT)
MS240-BZ	120V AC, 240°, 500W Max Load, OUTDOOR MOTION SENSOR (BRONZE)
MS-PC	120V AC, Optional Photocell Component for the above series security lights, Incl. WH & BZ trims to match security light color

LIGHTING SPECIFICATIONS:

- Dimming: Dimmable
- Cover Type: clear lens
- Total lumens: 4800LM
- Color temperature: 5000K/3000K
- Color rendering index: >80
- Light Beam Angle: 120°

WARRANTY: 7 years