

## SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 60 WATTS

### SPECIFICATIONS:

<b>WATTAGE:</b>	60W
<b>MODEL #:</b>	UFL06
<b>LISTINGS</b>	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
<b>VOLTAGE:</b>	100VAC-277VAC
<b>POWER FACTOR:</b>	>0.95
<b>FREQUENCY:</b>	50-60Hz
<b>LUMENS:</b>	9,360 Lumens
<b>LUMENS EFFICACY:</b>	>150 Lm/W
<b>KELVINS (CCT) AVAILABLE:</b>	3000K, 4000K, 5000K, 5700K, 6500K
<b>THD:</b>	12.7%
<b>CRI:</b>	>80
<b>IP RATING:</b>	IP66 (Suitable for Indoor or Outdoor Use)
<b>BEAM ANGLES (DEGREES) AVAILABLE:</b>	120° (standard), 90° & 60° (optional)
<b>MOUNTING INCLUDED:</b>	Hook (for Chain Mount, Chain Optional)
<b>MOUNTING OPTIONS:</b>	180° Adj. U Bracket, Pendant Mount
<b>ACCESSORIES:</b>	Aluminum or Prismatic Reflector; Sensor
<b>CONSTRUCTION:</b>	Anodized Aluminum
<b>LED CHIPS:</b>	Phillips
<b>LED DRIVER:</b>	Meanwell
<b>LIFE SPAN (HOURS):</b>	100,000H
<b>DIMMING COMPATIBLE:</b>	No
<b>LENGTH OF WARRANTY (YEARS):</b>	5 YEARS
<b>WORKING ENVIRONMENT:</b>	-45°C to +50°C (-49°F to +122°F)
<b>SUGGESTED REPLACEMENT FOR:</b>	150-175W HID
<b>POWER EFFICIENCY:</b>	>90%
<b>PRODUCT DIMENSIONS:</b>	<b>11" Diameter x 4½" Height</b>



**MOTION+DAYLIGHT  
SENSOR**



**60° ALUMINUM  
REFLECTOR**



**PRISMATIC  
REFLECTOR, WITH  
OR WITHOUT  
BOTTOM LENS**

### Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

### Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.



## SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 100 WATTS

### SPECIFICATIONS:

<b>WATTAGE:</b>	100W
<b>MODEL #:</b>	UFL10
<b>LISTINGS</b>	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
<b>VOLTAGE:</b>	100VAC-277VAC
<b>POWER FACTOR:</b>	>0.95
<b>FREQUENCY:</b>	50-60Hz
<b>LUMENS:</b>	15,600 Lumens
<b>LUMENS EFFICACY:</b>	>150 Lm/W
<b>KELVINS (CCT) AVAILABLE:</b>	3000K, 4000K, 5000K, 5700K, 6500K
<b>THD:</b>	12.7%
<b>CRI:</b>	>80
<b>IP RATING:</b>	IP66 (Suitable for Indoor or Outdoor Use)
<b>BEAM ANGLES (DEGREES) AVAILABLE:</b>	120° (standard), 90° & 60° (optional)
<b>MOUNTING INCLUDED:</b>	Hook (for Chain Mount, Chain Optional)
<b>MOUNTING OPTIONS:</b>	180° Adj. U Bracket, Pendant Mount
<b>ACCESSORIES:</b>	Aluminum or Prismatic Reflector; Sensor
<b>CONSTRUCTION:</b>	Anodized Aluminum
<b>LED CHIPS:</b>	Phillips
<b>LED DRIVER:</b>	Meanwell
<b>LIFE SPAN (HOURS):</b>	100,000H
<b>DIMMING COMPATIBLE:</b>	Yes, 0-10V Dimmable
<b>LENGTH OF WARRANTY (YEARS):</b>	5 YEARS
<b>WORKING ENVIRONMENT:</b>	-45°C to +50°C (-49°F to +122°F)
<b>SUGGESTED REPLACEMENT FOR:</b>	250-300W HID
<b>POWER EFFICIENCY:</b>	>90%
<b>PRODUCT DIMENSIONS:</b>	<b>11" Diameter x 4½" Height</b>



**MOTION+DAYLIGHT  
SENSOR**



**60° ALUMINUM  
REFLECTOR**



**PRISMATIC  
REFLECTOR, WITH  
OR WITHOUT  
BOTTOM LENS**

### Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

### Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.



Projects:

Comments:

## SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 150 WATTS

### SPECIFICATIONS:

<b>WATTAGE:</b>	150W
<b>MODEL #:</b>	UFL15
<b>LISTINGS</b>	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
<b>VOLTAGE:</b>	100VAC-277VAC
<b>POWER FACTOR:</b>	>0.95
<b>FREQUENCY:</b>	50-60Hz
<b>LUMENS:</b>	23,400 Lumens
<b>LUMENS EFFICACY:</b>	>150 Lm/W
<b>KELVINS (CCT) AVAILABLE:</b>	3000K, 4000K, 5000K, 5700K, 6500K
<b>THD:</b>	13.7%
<b>CRI:</b>	>80
<b>IP RATING:</b>	IP66 (Suitable for Indoor or Outdoor Use)
<b>BEAM ANGLES (DEGREES) AVAILABLE:</b>	120° (standard), 90° & 60° (optional)
<b>MOUNTING INCLUDED:</b>	Hook (for Chain Mount, Chain Optional)
<b>MOUNTING OPTIONS:</b>	180° Adj. U Bracket, Pendant Mount
<b>ACCESSORIES:</b>	Aluminum or Prismatic Reflector; Sensor
<b>CONSTRUCTION:</b>	Anodized Aluminum
<b>LED CHIPS:</b>	Phillips
<b>LED DRIVER:</b>	Meanwell
<b>LIFE SPAN (HOURS):</b>	100,000H
<b>DIMMING COMPATIBLE:</b>	Yes, 0-10V Dimmable
<b>LENGTH OF WARRANTY (YEARS):</b>	5 YEARS
<b>WORKING ENVIRONMENT:</b>	-45°C to +50°C (-49°F to +122°F)
<b>SUGGESTED REPLACEMENT FOR:</b>	400-500W HID
<b>POWER EFFICIENCY:</b>	>90%
<b>PRODUCT DIMENSIONS:</b>	<b>14.17" Diameter x 5.35" Height</b>



**MOTION+DAYLIGHT  
SENSOR**



**60° ALUMINUM  
REFLECTOR**



**PRISMATIC  
REFLECTOR, WITH  
OR WITHOUT  
BOTTOM LENS**

### Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

### Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.



## SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 200 WATTS

### SPECIFICATIONS:

<b>WATTAGE:</b>	200W
<b>MODEL #:</b>	UFL20
<b>LISTINGS</b>	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
<b>VOLTAGE:</b>	100VAC-277VAC
<b>POWER FACTOR:</b>	>0.95
<b>FREQUENCY:</b>	50-60Hz
<b>LUMENS:</b>	31,200 Lumens
<b>LUMENS EFFICACY:</b>	>150 Lm/W
<b>KELVINS (CCT) AVAILABLE:</b>	3000K, 4000K, 5000K, 5700K, 6500K
<b>THD:</b>	14.8%
<b>CRI:</b>	>80
<b>IP RATING:</b>	IP66 (Suitable for Indoor or Outdoor Use)
<b>BEAM ANGLES (DEGREES) AVAILABLE:</b>	120° (standard), 90° & 60° (optional)
<b>MOUNTING INCLUDED:</b>	Hook (for Chain Mount, Chain Optional)
<b>MOUNTING OPTIONS:</b>	180° Adj. U Bracket, Pendant Mount
<b>ACCESSORIES:</b>	Aluminum or Prismatic Reflector; Sensor
<b>CONSTRUCTION:</b>	Anodized Aluminum
<b>LED CHIPS:</b>	Phillips
<b>LED DRIVER:</b>	Meanwell
<b>LIFE SPAN (HOURS):</b>	100,000H
<b>DIMMING COMPATIBLE:</b>	Yes, 0-10V Dimmable
<b>LENGTH OF WARRANTY (YEARS):</b>	5 YEARS
<b>WORKING ENVIRONMENT:</b>	-45°C to +50°C (-49°F to +122°F)
<b>SUGGESTED REPLACEMENT FOR:</b>	600-750W HID
<b>POWER EFFICIENCY:</b>	>90%
<b>PRODUCT DIMENSIONS:</b>	<b>16.54" Diameter x 5.47" Height</b>



### Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

### Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.





Projects:

Comments:

## SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 240 WATTS

### SPECIFICATIONS:

<b>WATTAGE:</b>	240W
<b>MODEL #:</b>	UFL24
<b>LISTINGS</b>	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
<b>VOLTAGE:</b>	100VAC-277VAC
<b>POWER FACTOR:</b>	>0.95
<b>FREQUENCY:</b>	50-60Hz
<b>LUMENS:</b>	37,440 Lumens
<b>LUMENS EFFICACY:</b>	>150 Lm/W
<b>KELVINS (CCT) AVAILABLE:</b>	3000K, 4000K, 5000K, 5700K, 6500K
<b>THD:</b>	14.8%
<b>CRI:</b>	>80
<b>IP RATING:</b>	IP66 (Suitable for Indoor or Outdoor Use)
<b>BEAM ANGLES (DEGREES) AVAILABLE:</b>	120° (standard), 90° & 60° (optional)
<b>MOUNTING INCLUDED:</b>	Hook (for Chain Mount, Chain Optional)
<b>MOUNTING OPTIONS:</b>	180° Adj. U Bracket, Pendant Mount
<b>ACCESSORIES:</b>	Aluminum or Prismatic Reflector; Sensor
<b>CONSTRUCTION:</b>	Anodized Aluminum
<b>LED CHIPS:</b>	Phillips
<b>LED DRIVER:</b>	Meanwell
<b>LIFE SPAN (HOURS):</b>	100,000H
<b>DIMMING COMPATIBLE:</b>	Yes, 0-10V Dimmable
<b>LENGTH OF WARRANTY (YEARS):</b>	5 YEARS
<b>WORKING ENVIRONMENT:</b>	-45°C to +50°C (-49°F to +122°F)
<b>SUGGESTED REPLACEMENT FOR:</b>	750-1,000W HID
<b>POWER EFFICIENCY:</b>	>90%
<b>PRODUCT DIMENSIONS:</b>	<b>16.54" Diameter x 5.47" Height</b>



**MOTION+DAYLIGHT  
SENSOR**



**60° ALUMINUM  
REFLECTOR**



**PRISMATIC  
REFLECTOR, WITH  
OR WITHOUT  
BOTTOM LENS**

### Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

### Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.

