

Projects:

Comments:

SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 240 WATTS

SPECIFICATIONS:

WATTAGE:	240W
MODEL #:	UFL24
LISTINGS	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
VOLTAGE:	100VAC-277VAC
POWER FACTOR:	>0.95
FREQUENCY:	50-60Hz
LUMENS:	37,440 Lumens
LUMENS EFFICACY:	>150 Lm/W
KELVINS (CCT) AVAILABLE:	3000K, 4000K, 5000K, 5700K, 6500K
THD:	14.8%
CRI:	>80
IP RATING:	IP66 (Suitable for Indoor or Outdoor Use)
BEAM ANGLES (DEGREES) AVAILABLE:	120° (standard), 90° & 60° (optional)
MOUNTING INCLUDED:	Hook (for Chain Mount, Chain Optional)
MOUNTING OPTIONS:	180° Adj. U Bracket, Pendant Mount
ACCESSORIES:	Aluminum or Prismatic Reflector; Sensor
CONSTRUCTION:	Anodized Aluminum
LED CHIPS:	Phillips
LED DRIVER:	Meanwell
LIFE SPAN (HOURS):	100,000H
DIMMING COMPATIBLE:	Yes, 0-10V Dimmable
LENGTH OF WARRANTY (YEARS):	5 YEARS
WORKING ENVIRONMENT:	-45°C to +50°C (-49°F to +122°F)
SUGGESTED REPLACEMENT FOR:	750-1,000W HID
POWER EFFICIENCY:	>90%
PRODUCT DIMENSIONS:	16.54" Diameter x 5.47" Height



Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.



Projects:

Comments:

SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 200 WATTS

SPECIFICATIONS:

WATTAGE:	200W
MODEL #:	UFL20
LISTINGS	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
VOLTAGE:	100VAC-277VAC
POWER FACTOR:	>0.95
FREQUENCY:	50-60Hz
LUMENS:	31,200 Lumens
LUMENS EFFICACY:	>150 Lm/W
KELVINS (CCT) AVAILABLE:	3000K, 4000K, 5000K, 5700K, 6500K
THD:	14.8%
CRI:	>80
IP RATING:	IP66 (Suitable for Indoor or Outdoor Use)
BEAM ANGLES (DEGREES) AVAILABLE:	120° (standard), 90° & 60° (optional)
MOUNTING INCLUDED:	Hook (for Chain Mount, Chain Optional)
MOUNTING OPTIONS:	180° Adj. U Bracket, Pendant Mount
ACCESSORIES:	Aluminum or Prismatic Reflector; Sensor
CONSTRUCTION:	Anodized Aluminum
LED CHIPS:	Phillips
LED DRIVER:	Meanwell
LIFE SPAN (HOURS):	100,000H
DIMMING COMPATIBLE:	Yes, 0-10V Dimmable
LENGTH OF WARRANTY (YEARS):	5 YEARS
WORKING ENVIRONMENT:	-45°C to +50°C (-49°F to +122°F)
SUGGESTED REPLACEMENT FOR:	600-750W HID
POWER EFFICIENCY:	>90%
PRODUCT DIMENSIONS:	16.54" Diameter x 5.47" Height



Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.



Projects:

Comments:

SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 150 WATTS

SPECIFICATIONS:

WATTAGE:	150W
MODEL #:	UFL15
LISTINGS	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
VOLTAGE:	100VAC-277VAC
POWER FACTOR:	>0.95
FREQUENCY:	50-60Hz
LUMENS:	23,400 Lumens
LUMENS EFFICACY:	>150 Lm/W
KELVINS (CCT) AVAILABLE:	3000K, 4000K, 5000K, 5700K, 6500K
THD:	13.7%
CRI:	>80
IP RATING:	IP66 (Suitable for Indoor or Outdoor Use)
BEAM ANGLES (DEGREES) AVAILABLE:	120° (standard), 90° & 60° (optional)
MOUNTING INCLUDED:	Hook (for Chain Mount, Chain Optional)
MOUNTING OPTIONS:	180° Adj. U Bracket, Pendant Mount
ACCESSORIES:	Aluminum or Prismatic Reflector; Sensor
CONSTRUCTION:	Anodized Aluminum
LED CHIPS:	Phillips
LED DRIVER:	Meanwell
LIFE SPAN (HOURS):	100,000H
DIMMING COMPATIBLE:	Yes, 0-10V Dimmable
LENGTH OF WARRANTY (YEARS):	5 YEARS
WORKING ENVIRONMENT:	-45°C to +50°C (-49°F to +122°F)
SUGGESTED REPLACEMENT FOR:	400-500W HID
POWER EFFICIENCY:	>90%
PRODUCT DIMENSIONS:	14.17" Diameter x 5.35" Height



**MOTION+DAYLIGHT
SENSOR**



**60° ALUMINUM
REFLECTOR**



**PRISMATIC
REFLECTOR, WITH
OR WITHOUT
BOTTOM LENS**

Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.



Projects:

Comments:

SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 100 WATTS

SPECIFICATIONS:

WATTAGE:	100W
MODEL #:	UFL10
LISTINGS	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
VOLTAGE:	100VAC-277VAC
POWER FACTOR:	>0.95
FREQUENCY:	50-60Hz
LUMENS:	15,600 Lumens
LUMENS EFFICACY:	>150 Lm/W
KELVINS (CCT) AVAILABLE:	3000K, 4000K, 5000K, 5700K, 6500K
THD:	12.7%
CRI:	>80
IP RATING:	IP66 (Suitable for Indoor or Outdoor Use)
BEAM ANGLES (DEGREES) AVAILABLE:	120° (standard), 90° & 60° (optional)
MOUNTING INCLUDED:	Hook (for Chain Mount, Chain Optional)
MOUNTING OPTIONS:	180° Adj. U Bracket, Pendant Mount
ACCESSORIES:	Aluminum or Prismatic Reflector; Sensor
CONSTRUCTION:	Anodized Aluminum
LED CHIPS:	Phillips
LED DRIVER:	Meanwell
LIFE SPAN (HOURS):	100,000H
DIMMING COMPATIBLE:	Yes, 0-10V Dimmable
LENGTH OF WARRANTY (YEARS):	5 YEARS
WORKING ENVIRONMENT:	-45°C to +50°C (-49°F to +122°F)
SUGGESTED REPLACEMENT FOR:	250-300W HID
POWER EFFICIENCY:	>90%
PRODUCT DIMENSIONS:	11" Diameter x 4½" Height



Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.



SUPERCHIP™ PRO SERIES LED UFO HIGH BAY / LOW BAY, 60 WATTS

SPECIFICATIONS:

WATTAGE:	60W
MODEL #:	UFL06
LISTINGS	ETL, cETL, DLC 4.2, CE RoHS, TUV, FCC
VOLTAGE:	100VAC-277VAC
POWER FACTOR:	>0.95
FREQUENCY:	50-60Hz
LUMENS:	9,360 Lumens
LUMENS EFFICACY:	>150 Lm/W
KELVINS (CCT) AVAILABLE:	3000K, 4000K, 5000K, 5700K, 6500K
THD:	12.7%
CRI:	>80
IP RATING:	IP66 (Suitable for Indoor or Outdoor Use)
BEAM ANGLES (DEGREES) AVAILABLE:	120° (standard), 90° & 60° (optional)
MOUNTING INCLUDED:	Hook (for Chain Mount, Chain Optional)
MOUNTING OPTIONS:	180° Adj. U Bracket, Pendant Mount
ACCESSORIES:	Aluminum or Prismatic Reflector; Sensor
CONSTRUCTION:	Anodized Aluminum
LED CHIPS:	Phillips
LED DRIVER:	Meanwell
LIFE SPAN (HOURS):	100,000H
DIMMING COMPATIBLE:	No
LENGTH OF WARRANTY (YEARS):	5 YEARS
WORKING ENVIRONMENT:	-45°C to +50°C (-49°F to +122°F)
SUGGESTED REPLACEMENT FOR:	150-175W HID
POWER EFFICIENCY:	>90%
PRODUCT DIMENSIONS:	11" Diameter x 4½" Height



Features:

Industrial die cast anodized aluminum fixture housing (powdercoated in Black) offers excellent resistance to corrosion, UV degradation, impact and abrasion. IP66 waterproof, dust-proof, explosion-proof and corrosion resistant. Optional 180° adjustable "U" mounting bracket allows for easy, optimum placement of light. Polycarbonate clear lens for durability and clarity. Innovative modular fin heatsink design provides maximum heat dissipation, maximizing the life of the fixture.

Applications:

Warehouse facilities, manufacturing facilities, workshops, convention centers, exhibition halls, sporting arenas, big-box retail stores, large supermarkets, cold garage facilities, storeroom, toll stations, gas stations, and gymnasiums.

