

Proje	ects:		
Com	ments:		

CW41L - STAINLESS STEEL 120V/277V LED IN-GROUND WELL LIGHT

SPECIFICATIONS:

5. <u>2</u> 66.1				
WATTAGES:	11W, 15W, 20W, 30W or 50W			
MODEL #:	CW41L			
LISTINGS	ETL, cETL, CE RoHS, TUV, FCC			
VOLTAGE:	100V~130V, 170V~240V or 265V~277V AC			
POWER FACTOR:	>0.95			
FREQUENCY:	50-60Hz			
LUMENS:	900 to 4,500 Lumens (depending on wattage)			
LUMENS EFFICACY:	>80 Lm/W			
KELVIN (CCT):	2700K, 3000K, 4000K or 5000K			
THD:	14.7%			
CRI:	>80			
IP RATING:	IP65 Outdoor / Wet Location Use			
BEAM ANGLE (DEGREE):	25°, 40°, 110° (Consult Factory for others)			
MOUNTING:	PVC Sleeve Included for In-Ground Mounting			
MATERIALS:	304 Stainless Steel Top, Cast Aluminum Housing			
USED FOR:	Commercial / Residential Landscapes			
APPLICATIONS:	Wall Washing, Tree / Flag Pole Uplighting, etc.			
LIFE SPAN (HOURS):	50,000+ Hours			
DIMMING COMPATIBLE:	Dimmable (depending on LED options, consult factory)			
LENGTH OF WARRANTY (YEARS):	One year (Fixture), 5 years (LED components)			
WORKING ENVIRONMENT:	-34°C to +50°C (-30°F to +122°F)			
SUGGESTED REPLACEMENT FOR:	90-500 Watt Halogen (30-175W Metal Halide)			
POWER EFFICIENCY:	>90%			
PERCENTAGE OF WATTAGE SAVED:	66-90% Versus HID or Halogen			















